# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

070308015

N/A



Page: 1of 5

First issue: Dec. 26, 2007 Revised: Apr. 10, 2008 MSDS No.: BHM018

Product name: LC61M, LC65HY-M, LC980M, LC1100M, LC1100HY-M, LC38M, LC67M, LC990M

# MATERIAL SAFETY DATA SHEET

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

LC980M LC1100M Product Name LC65HY-M LC61M LK3573001 Product Code LK3367001 LK3292001 LK3375001 LC990M Product Name LC1100HY-M LC38M LC67M LK3670001 LK3650001 Product Code LK3531001 LK3662001

General Use Inkjet printing

Product Description Water based ink cartridge for inkjet printing machine

MSDS No. BHM018

Manufacturer BROTHER INDUSTRIES, LTD.

5-1, Hamada-cho, Minami-ku, Nagoya 457-0822, JAPAN Telephone Number for Information +81-52-824-3429

Importer BROTHER INTERNATIONAL CORPORATION

in USA 100 Somerset Corporate Boulevard, P.O.Box 6911, Bridgewater,

NJ 08807-0911, USA

Telephone Number for Information +1-800-284-4329

Importer BROTHER INTERNATIONAL CORP. (Canada) LTD.

in Canada 1 rue Hôtel de Ville, Dollard-des-Ormeaux, Québec, H9B 3H6, CANADA

Telephone Number for Information +1-514-685-0600

Importer BROTHER INTERNATIONAL (AUST.) PTY. LTD. ACN 001 393 835

in Australia 7 Khartoum Road, North Ryde, N.S.W. 2113 08875-6714, AUSTRALIA

Telephone Number for Information +61-2-9887-4344

Importer BROTHER INTERNATIONAL EUROPE LTD.

in Europe Brother house, 1 Tame Street, Guide Bridge, Audenshaw, Manchester

M34 5JE, UK

Telephone Number for Information +44-161-330-6531

Please telephone to the above office during our business hours.

#### 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

Ink in cartridge is dark red liquid with slight odor.

Keep out of reach of children.

Ink poses little or no immediate hazard if spilled.

#### POTENTIAL HEALTH EFFECTS

Inhalation: Not expected to be a route of exposure under normal use

Eye: Ink may cause slight irritation.

Skin: Prolonged exposure to ink may cause irritation.

Ingestion: Ink may cause gastrointestinal or other adverse effects.



Page: 2of 5

First issue: Dec. 26, 2007 Revised: Apr. 10, 2008 MSDS No.: BHM018

Product name: LC61M, LC65HY-M, LC980M, LC1100M, LC1100HY-M,

LC38M, LC67M, LC990M

# MATERIAL SAFETY DATA SHEET

#### CHRONIC EFFECTS / CARCINOGENICITY

Ingredients of ink have not been classified as carcinogens according to IARC monographs, NTP, and OSHA regulated.

#### EU HAZARD LABEL

Ink is not classified according to EU-Directive 1999/45/EC. But ink has to bear the inscription: "Contains water soluble heterocyclic magenta azo dye compounds. May produce an allergic reaction."

CHEMICAL NAME	CAS# / EC#	% by weight	USA OSHA PEL	ACGIH TLV	EU Symbol / Risk Phrases
Glycerol	56-81-5 / 200-289-5	10 - 30	(as mist) Total dust TWA 15mg/m <sup>3</sup> Respirable fraction TWA 5mg/m <sup>3</sup>	(as mist) Total dust TWA 10mg/m <sup>3</sup>	Not classified
Diethylene glycol	111-46-6 / 203-872-2	1-5	Not established	Not established	Xn / R22
Magenta dye	Registered	1 – 4	Not established	Not established	Xi / R36 Xi / R43 N / R51/53
Water	7732-18-5 / 231-791-2	50 - 70	Not established	Not established	Not classified

# 4. FIRST AID MEASURES

INHALATION:

Remove to fresh air area and get medical attention.

EYE:

Flush immediately with running water for at least 15 minutes and get

medical attention.

SKIN:

Wash with water and soap.

INGESTION:

Dilute with water and get medical attention.

#### 5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

Auto-ignition temperature:

444°C

Flammability:

LEL: Not available UEL: Not available

Flash point: Does not flash (>93.3°C)

(Tag closed cup & Cleveland opened cup)

EXTINGUISHING MEDIA

Suitable:

Water, CO<sub>2</sub>, Foam, Dry chemical.

Not to be used:

None



Page: 3of 5

First issue: Dec. 26, 2007 Revised: Apr. 10, 2008 MSDS No.: BHM018

Product name: LC61M, LC65HY-M, LC980M, LC1100M, LC1100HY-M,

LC38M, LC67M, LC990M

# MATERIAL SAFETY DATA SHEET

FIRE FIGHTING INSTRUCTIONS

Special exposure hazards: Refer to section 10.

Special protect equipment for fire-fighters: Use self-contained breathing apparatus.

# 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTION: In case of ink vapor formation use respirator.

ENVIRONMENTAL PRECAUTION: Take care to minimize ink that reaches to a sewer.

METHODES FOR CLEANING UP: Wipe up ink with absorbent towel. Wash with water to remove remaining traces of ink.

# 7. HANDLING AND STORAGE

HANDLING: Avoid skin contact with ink. Prevent eye contact with ink.

STORAGE: Keep out of reach of children. Store in a cool, dark, and dry place.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMIT VALUES: Refer to section 2.

EXPOSURE CONTROLS

Engineering controls: Ventilation is not required under normal use.

Personal protection

Respiratory protection:

Hand protection:

Not required under normal use.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dark red liquid

Auto-ignition temperature: 444°C
Boiling point: 103°C
Density: 1.06g/ml

Flammability: LEL: Not available UEL: Not available

Flash point: Does not flash (>93.3°C)

(Tag closed cup & Cleveland opened cup)

Freezing point : -8°C

Odor: Slight odor Partition coefficient (n-octanol/water): Not available

pH: 7-9
Solubility in water: Soluble
Vapor density (Air=1): Not available
Vapor pressure: Not available

Viscosity: 2 - 5 mPa·s



Product name: LC61M, LC65HY-M, LC980M, LC1100M, LC1100HY-M,

Page: 4of 5

First issue: Dec. 26, 2007 Revised: Apr. 10, 2008 MSDS No.: BHM018

## MATERIAL SAFETY DATA SHEET

# 10. STABILITY AND REACTIVITY

STABILITY:

Stable

CONDITIONS TO AVOID:

None

MATERIALS TO AVOID:

Strong oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS:

LC38M, LC67M, LC990M

Carbon monoxide, Carbon dioxide

HAZARDOUS POLYMERIZATION:

Does not occur

# 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity:

LD50 of ink is greater than 2000mg/kg.

Eye irritation: Skin irritation: Ink is classified as a MILD IRRITANT. Ink is classified as a NON IRRITANT.

# 12. ECOLOGICAL INFORMATION

PERSISTENCE AND DEGRADABILITY:

Not available

BIOACCUMULATIVE POTENTIAL:

Not available

# 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with federal, state and local regulations.

### 14. TRANSPORT INFORMATION

US DEPARTMENT OF TRANSPORTATION (DOT):

Not applicable

MARITIME TRANSPORT IMDG:

Not applicable

AIR TRANSPORT ICAO/IATA:

Not applicable

### 15. REGULATORY INFORMATION

US REGULATIONS

TSCA STATUS:

All components in ink are listed on TSCA inventory.

**EUROPEAN REGULATIONS** 

EU NOTIFICATION:

All components in ink are listed on EINECS, ELINCS or NLP

inventory.

EU HAZARD LABEL:

Ink is not classified according to EU-Directive 1999/45/EC. But ink

has to bear the inscription: "Contains water soluble heterocyclic magenta azo dye compounds. May produce an allergic reaction."

# 16. OTHER INFORMATION

The information relates only to this specific ink cartridge. It may not be valid for this ink cartridge, if used in combination with any other materials or in any other process. And it is based on our best knowledge as of the date of preparation (revision).



Product name: LC61M, LC65HY-M, LC980M, LC1100M, LC1100HY-M, LC38M, LC67M, LC990M

Page: 5of 5

First issue: Dec. 26, 2007 Revised: Apr. 10, 2008 MSDS No.: BHM018

### MATERIAL SAFETY DATA SHEET

EU Hazard Symbols:

Xi: Irritant

Xn: Harmful

N: Dangerous for the environment

EU Risk (R) Phrase definitions:

R22: Harmful if swallowed.

R36: Irritating to eyes.

R43: May cause sensitization by skin contact.

R51/53: Toxic to aquatic organisms may cause long-term

adverse effects in the aquatic environment.

Key

ACGIH TLV (Threshold Limit Value) under American Conference of Governmental

Industrial Hygienists

DOT Department Of Transportation (USA)

EINECS European Inventory of Existing Commercial Chemical Substances (EU)

ELINCS European List of Notified Chemical Substances (EU)

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Degree Goods

IMDG International Maritime Dangerous Goods

NLP No-Longer Polymers List (EU) NTP National Toxicology Program (USA)

OSHA Occupational Safety and Health Administration (USA)

OSHA HCS Hazard Communication Standard issued by Occupational Safety and Health

Administration (USA)

OSHA PEL PEL (Permissible Exposure Limit) under Occupational Safety and Health

Administration (USA)

TSCA Toxic Substances Control Act (USA)