# This SDS packet was issued with item:

078037140

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

078037157



Revision date: 16-Sep-2014 Version: 2.2 Page 1 of 11

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

**Product Identifier** 

Material Name: Nolvadent®

Trade Name: NOLVADENT®

Chemical Family: Mixture

Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Intended Use: Veterinary product Restrictions on Use: Not for human use

Details of the Supplier of the Safety Data Sheet

Zoetis Inc. 100 Campus Drive, P.O. Box 651 Florham Park, New Jersey 07932 (USA)

Rocky Mountain Poison Control Center Phone: 1-866-531-8896

Product Support/Technical Services Phone: 1-800-366-5288

Zoetis Belgium S.A. Mercuriusstraat 20 1930 Zaventem

Belgium

**Emergency telephone number:** 

CHEMTREC (24 hours): 1-800-424-9300

Contact E-Mail: VMIPSrecords@zoetis.com

Emergency telephone number:

International CHEMTREC (24 hours): +1-703-527-3887

# 2. HAZARDS IDENTIFICATION

Appearance: Clear pink liquid

Classification of the Substance or Mixture

**GHS - Classification** 

Acute Toxicity - Dusts and Mists: Category 4 Acute aquatic toxicity: Category 2

Chronic aquatic toxicity: Category 2
Flammable liquids- Category 3

**EU Classification:** 

EU Indication of danger: T - Toxic

N - Dangerous for the environment

EU Risk Phrases:

R23 - Toxic by inhalation.

R10 - Flammable.

R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

**Label Elements** 

Signal Word: Warning

\_\_\_\_\_

Material Name: Nolvadent® Page 2 of 11
Revision date: 16-Sep-2014 Version: 2.2

## 2. HAZARDS IDENTIFICATION

Hazard Statements: H332 - Harmful if inhaled

H226 - Flammable liquid and vapor

H411 - Toxic to aquatic life with long lasting effects

**Precautionary Statements:** P271 - Use only outdoors or in a well-ventilated area

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P264 - Wash hands thoroughly after handling

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P240 - Ground/Bond container and receiving equipment
P243 - Take precautionary measures against static discharge
P241 - Use explosion-proof electrical/ventilating/lighting/equipment

P242 - Use only non-sparking tools P233 - Keep container tightly closed

P403 + P235 - Store in a well-ventilated place. Keep cool

P273 - Avoid release to the environment

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower

P312 - Call a POISON CENTRE/doctor/physician if you feel unwell

P391 - Collect spillage

P501 - Dispose of contents/container in accordance with all local and national regulations



Other Hazards Short Term:

Vapors may cause drowsiness and dizziness. May cause respiratory tract irritation. May cause eye irritation May cause slight skin irritation. May be harmful if swallowed. Individuals sensitive to this chemical or other materials in its chemical class may develop allergic reactions. May cause liver and kidney effects

Australian Hazard Classification (NOHSC):

Hazardous Substance. Dangerous Goods.

Note:

This document has been prepared in accordance with standards for workplace safety, which requires the inclusion of all known hazards of the product or its ingredients regardless of the potential risk. The precautionary statements and warning included may not apply in all cases. Your needs may vary depending upon the potential for exposure in your workplace.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous

Page 3 of 11 Material Name: Nolvadent® Revision date: 16-Sep-2014 Version: 2.2

| 3. COMPOSITION/INFORMATION ON INGREDIENTS |            |                             |                                     |   |   |  |
|---|------------|-----------------------------|-------------------------------------|---|---|--|
| Ingredient                                | CAS Number | EU<br>EINECS/ELINCS<br>List | EU Classification                   | GHS<br>Classification   | % |  |
| Chlorhexidine acetate                     | 56-95-1    | 200-302-4                   | Xn;R22<br>Xi;R36<br>T+;R26<br>N;R50 | Acute Tox. 4 (H302) Acute Tox.2(H330) Eye Irrit.2A (H319) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) | 2 |  |
| Ethyl alcohol (ethanol)                   | 64-17-5    | 200-578-6                   | F; R11                              | Flam. Liq. 2 (H225)   | 6 |  |

Additional Information: Ingredient(s) indicated as hazardous have been assessed under standards for workplace

safety.

For the full text of the R phrases and CLP/GHS abbreviations mentioned in this Section, see Section 16

## 4. FIRST AID MEASURES

**Description of First Aid Measures** 

**Eye Contact:** Flush with water while holding eyelids open for at least 15 minutes. Seek medical attention

immediately.

**Skin Contact:** Remove contaminated clothing. Flush area with large amounts of water. Use soap. Seek

medical attention.

Ingestion: Never give anything by mouth to an unconscious person. Wash out mouth with water. Do not

induce vomiting unless directed by medical personnel. Seek medical attention immediately.

Inhalation: Remove to fresh air and keep patient at rest. Seek medical attention immediately.

Most Important Symptoms and Effects, Both Acute and Delayed

For information on potential signs and symptoms of exposure, See Section 2 - Hazards Symptoms and Effects of

Exposure: Identification and/or Section 11 - Toxicological Information.

**Medical Conditions** None known

Aggravated by Exposure:

Indication of the Immediate Medical Attention and Special Treatment Needed

Notes to Physician:

## 5. FIRE-FIGHTING MEASURES

Extinguish fires with CO2, extinguishing powder or foam. **Extinguishing Media:** 

Special Hazards Arising from the Substance or Mixture

**Hazardous Combustion** Formation of toxic gases is possible during heating or fire. May include oxides of carbon

Products: nitrogen and products of chlorine

Fire / Explosion Hazards: Vapors will form flammable or explosive mixtures with air at room temperature. Fine particles

(such as dust and mists) may fuel fires/explosions. Flammable liquid and vapor

**Advice for Fire-Fighters** 

During all fire fighting activities, wear appropriate protective equipment, including self-contained breathing apparatus. Use sparkproof tools and explosion-proof equipment

Material Name: Nolvadent® Page 4 of 11
Revision date: 16-Sep-2014 Version: 2.2

\_\_\_\_\_

## 6. ACCIDENTAL RELEASE MEASURES

#### Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Eliminate all sources of ignition and ventilate area using explosion-proof equipment. Personnel involved in clean-up should wear appropriate personal protective equipment (see Section 8). Minimize exposure.

#### **Environmental Precautions**

Place waste in an appropriately labeled, sealed container for disposal. Care should be taken to avoid environmental release.

#### Methods and Material for Containment and Cleaning Up

Measures for Cleaning /

Collecting:

Contain the source of the spill if it is safe to do so. Eliminate possible ignition sources (e.g., heat, sparks, flame, impact, friction, electricity). Use non-combustible absorbent material to wipe up spill and place in a sealed container for disposal. Clean contaminated surface thoroughly.

Additional Consideration for

Large Spills:

Eliminate possible ignition sources (e.g., heat, sparks, flame, impact, friction, electricity), and follow appropriate grounding procedures. Contain the source of the spill or leak if it is safe to do so. Collect spill with a non-combustible absorbent material and transfer to labeled container for disposal. Clean spill area thoroughly. Non-essential personnel should be evacuated from affected area. Report emergency situations immediately. Clean up operations should only be undertaken by trained personnel.

## 7. HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Flammable liquid and vapor- keep away from ignition sources and clean up spills promptly. Eliminate possible ignition sources (e.g., heat, sparks, flame, impact, friction, electricity), and follow appropriate grounding and bonding procedures. Avoid contact with eyes, skin, and clothing. Use appropriate personal protective equipment. Wash thoroughly after handling. Use with adequate ventilation. Avoid breathing vapor or mist. Releases to the environment should be avoided. Review and implement appropriate technical and procedural waste water and waste disposal measures to prevent occupational exposure or environmental releases. Potential points of process emissions of this material to the atmosphere should be controlled with dust collectors, HEPA filtration systems or other equivalent controls.

#### Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions: Keep in a cool, well-ventilated place. Keep away from heat, sparks, flame, and other sources of

ignition.

Incompatible Materials: Acids, bases, and oxidizers

Specific end use(s): No data available

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Control Parameters**

Refer to available public information for specific member state Occupational Exposure Limits.

## Ethyl alcohol (ethanol)

Czech Republic OEL - TWA

 ACGIH Threshold Limit Value (STEL)
 1000 ppm

 Australia TWA
 1000 ppm

 1880 mg/m³
 1880 mg/m³

 Austria OEL - MAKS
 1000 ppm

 1900 mg/m³
 1907 mg/m³

 Belgium OEL - TWA
 1000 ppm

 1907 mg/m³
 1000.0 mg/m³

1000 mg/m<sup>3</sup>

Material Name: Nolvadent® Page 5 of 11
Revision date: 16-Sep-2014 Version: 2.2

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| 6. EXPUSURE CUNTRULS      | / PERSUN                             |
|---------------------------|--------------------------------------|
| Denmark OEL - TWA         | 1000 ppm                             |
|                           | 1900 mg/m <sup>3</sup>               |
| Estonia OEL - TWA         | 500 ppm                              |
|                           | 1000 mg/m <sup>3</sup>               |
| Finland OEL - TWA         | 1000 ppm                             |
|                           | 1900 mg/m <sup>3</sup>               |
| France OEL - TWA          | 1000 ppm                             |
| Comment TDOC 000 TIMA     | 1900 mg/m <sup>3</sup>               |
| Germany - TRGS 900 - TWAs | 500 ppm                              |
| Ones (DEO) MAK            | 960 mg/m <sup>3</sup>                |
| Germany (DFG) - MAK       | 500 ppm<br>960 mg/m <sup>3</sup>     |
| Greece OEL - TWA          | 1000 ppm                             |
| Greece OEL - TWA          | 1900 ppili<br>1900 mg/m <sup>3</sup> |
| Hungary OEL - TWA         | 1900 mg/m <sup>3</sup>               |
| Latvia OEL - TWA          | 1000 mg/m <sup>3</sup>               |
| Lithuania OEL - TWA       | 500 ppm                              |
| Litituania OLL - I WA     | 1000 mg/m <sup>3</sup>               |
| Netherlands OEL - TWA     | 260 mg/m <sup>3</sup>                |
| Vietnam OEL - TWAs        | 1000 mg/m <sup>3</sup>               |
| OSHA - Final PELS - TWAs: | 1000 mg/m                            |
| OOTA THICK LEG TWAS.      | 1900 mg/m <sup>3</sup>               |
| Poland OEL - TWA          | 1900 mg/m <sup>3</sup>               |
| Portugal OEL - TWA        | 1000 ppm                             |
| Romania OEL - TWA         | 1000 ppm                             |
|                           | 1900 mg/m <sup>3</sup>               |
| Slovakia OEL - TWA        | 500 ppm                              |
|                           | 960 mg/m <sup>3</sup>                |
| Slovenia OEL - TWA        | 1000 ppm                             |
|                           | 1900 mg/m <sup>3</sup>               |
| Spain OEL - TWA           | 1000 ppm                             |
|                           | 1910 mg/m <sup>3</sup>               |
| Sweden OEL - TWAs         | 500 ppm                              |
|                           | 1000 mg/m <sup>3</sup>               |
| Switzerland OEL -TWAs     | 500 ppm                              |
|                           | 960 mg/m <sup>3</sup>                |

The purpose of the Occupational Exposure Band (OEB) classification system is to separate substances into different Hazard categories when the available data are sufficient to do so, but inadequate to establish an Occupational Exposure Limit (OEL). The OEB given is based upon an analysis of all currently available data; as such, this value may be subject to revision when new information becomes available.

Chlorhexidine acetate

**Zoetis OEB** OEB 4 (control exposure to the range of 1ug/m³ to <10ug/m³)

**Exposure Controls** 

Engineering Controls: Engineering controls should be used as the primary means to control exposures. Keep air

contamination levels below the exposure limits or within the OEB range listed above in this

section.

**Personal Protective** 

Equipment:

Refer to applicable national standards and regulations in the selection and use of personal

protective equipment (PPE).

Hands: Impervious gloves are recommended if skin contact with drug product is possible and for bulk

processing operations.

ZT00060

Page 6 of 11 Material Name: Nolvadent® Version: 2.2 Revision date: 16-Sep-2014

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Wear safety glasses or goggles if eye contact is possible. Eves:

Skin: Impervious protective clothing is recommended if skin contact with drug product is possible and

for bulk processing operations.

Respiratory protection: If airborne exposures are within or exceed the Occupational Exposure Band (OEB) range, wear

an appropriate respirator with a protection factor sufficient to control exposures to the bottom of the OEB range. If the applicable Occupational Exposure Limit (OEL) is exceeded, wear an appropriate respirator with a protection factor sufficient to control exposures to below the OEL.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Color: Pink Liquid

Medicinal No data available. Odor: **Odor Threshold:** 

Mixture Molecular Formula: **Molecular Weight:** Mixture

**Solvent Solubility:** No data available

Water Solubility: Soluble

pH: No data available. Melting/Freezing Point (°C): No data available **Boiling Point (°C):** No data available. Partition Coefficient: (Method, pH, Endpoint, Value)

No data available

**Decomposition Temperature (°C):** No data available.

No data available **Evaporation Rate (Gram/s):** Vapor Pressure (kPa): No data available Vapor Density (g/ml): No data available **Relative Density:** No data available Viscosity: No data available

Flammablity:

Autoignition Temperature (Solid) (°C): No data available Flammability (Solids): No data available Flash Point (Liquid) (°C): 53.3°C / 128°F **Upper Explosive Limits (Liquid) (% by Vol.):** No data available No data available Lower Explosive Limits (Liquid) (% by Vol.):

## 10. STABILITY AND REACTIVITY

Reactivity: No data available

**Chemical Stability:** Stable under normal conditions of use.

**Possibility of Hazardous Reactions** 

No data available **Oxidizing Properties:** 

**Conditions to Avoid:** Extremes of temperature and direct sunlight. Fine particles (such as mists) may fuel

fires/explosions. Eliminate possible ignition sources (e.g., heat, sparks, flame, impact, friction,

electrostatic discharge).

**Incompatible Materials: Hazardous Decomposition** 

Acids, bases, and oxidizers

Products:

Toxic or corrosive oxides of carbon and nitrogen.

## 11. TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects

Page 7 of 11 Material Name: Nolvadent® Revision date: 16-Sep-2014 Version: 2.2

## 11. TOXICOLOGICAL INFORMATION

**General Information:** 

Toxicological properties of the formulation have not been investigated. The information included in this section describes the potential hazards of the individual ingredients.

#### Acute Toxicity: (Species, Route, End Point, Dose)

#### Chlorhexidine acetate

Mouse Oral LD 50 2000 mg/kg Rat Oral LD 50 (F) 1180 / (M) 1710 mg/kg 0.10 - 0.46 mg/L Rat Inhalation LC 50 Rabbit Dermal LD 50 > 2000 mg/kg

#### Ethyl alcohol (ethanol)

Mouse Oral LD50 3450 mg/kg Oral LD50 7060mg/kg Rat Inhalation LC50 10h 20,000ppm Rat

**Acute Toxicity Comments:** 

A greater than symbol (>) indicates that the toxicity endpoint being tested was not achievable

at the highest dose used in the test.

#### Irritation / Sensitization: (Study Type, Species, Severity)

#### Chlorhexidine acetate

Skin Irritation Rabbit Mild Eye Irritation Severe Rabbit

Skin Sensitization - GPMT Guinea Pig Negative

## Ethyl alcohol (ethanol)

Eye Irritation Rabbit Severe Skin Irritation Rabbit Mild

#### Repeated Dose Toxicity: (Duration, Species, Route, Dose, End Point, Target Organ)

#### Chlorhexidine acetate

500 mg/kg/day 13 Week(s) Rabbit Dermal LOAEL Liver, Skin

#### Reproduction & Developmental Toxicity: (Study Type, Species, Route, Dose, End Point, Effect(s))

## Chlorhexidine acetate

Embryo / Fetal Development Rat Oral 31.25 mg/kg/day LOEL Maternal toxicity

Embryo / Fetal Development Rat Oral 62.5 mg/kg/day **NOEL** No effects at maximum dose

#### Genetic Toxicity: (Study Type, Cell Type/Organism, Result)

#### Chlorhexidine acetate

Mammalian Cell Mutagenicity Mouse Lymphoma

In Vitro Cytogenetics Chinese Hamster Ovary (CHO) cells Negative

In Vivo Micronucleus Rat Hepatocyte Negative

ZT00060

Material Name: Nolvadent® Page 8 of 11
Revision date: 16-Sep-2014 Version: 2.2

\_\_\_\_\_

## 11. TOXICOLOGICAL INFORMATION

Carcinogen Status: Ethanol has been shown to be carcinogenic in long-term studies only when consumed as

alcoholic beverage None of the other components of this mixture are listed as a carcinogen by

IARC, NTP or OSHA.

Ethyl alcohol (ethanol)

IARC: Group 1 (Carcinogenic to Humans)

OSHA: Listed

**Product Level Toxicity Data** 

**Inhalation ATE (Acute Toxicity** 

Estimate), calculated

5 mg/l (dusts/mists)

# 12. ECOLOGICAL INFORMATION

**Environmental Overview:** Releases to the environment should be avoided. The environmental characteristics of this

mixture have not been fully evaluated. The following information is available for the individual

ingredients.

**Toxicity:** 

Aquatic Toxicity: (Species, Method, End Point, Duration, Result)

Chlorhexidine acetate

Oncorhynchus mykiss (Rainbow Trout) NA LC50 96 Hours 1.9 ppm Lepomis macrochirus (Bluegill Sunfish) N/A LC50 96 Hours 0.6 ppm

Daphnia Magna (Water Flea) N/A EC50 N/A 0.06 mg/L

Ethyl alcohol (ethanol)

Oncorhynchus mykiss (Rainbow Trout) LC50/96h 12,900-15,300 mg/L

Terrestrial Toxicity: (Species, Method, End Point, Duration, Result)

Chlorhexidine acetate

Colinus virginianus (Bobwhite Quail) N/A LD50 N/A 2013 mg/kg

Persistence and Degradability: No data available

Bio-accumulative Potential: No data available

Mobility in Soil: No data available

\_\_\_\_\_

Material Name: Nolvadent® Page 9 of 11
Revision date: 16-Sep-2014 Version: 2.2

\_\_\_\_\_

## 13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods: Waste of this product may qualify as a RCRA Hazardous Waste. Status should be confirmed

by testing for RCRA hazardous characteristics (i.e. corrosivity, toxicity, reactivity, or ignitability). Dispose of waste in accordance with all applicable laws and regulations. Member State specific and Community specific provisions must be considered. Considering the relevant known environmental and human health hazards of the material, review and implement appropriate technical and procedural waste water and waste disposal measures to prevent occupational exposure and environmental release. It is recommended that waste minimization be practiced. The best available technology should be utilized to prevent environmental releases. This may include destructive techniques for waste and wastewater.

## 14. TRANSPORT INFORMATION

The following refers to all modes of transportation unless specified below.

Domestically-non-restricted (alcohol content L/T 25%)

Transport according to the requirements of the appropriate regulatory body.

UN number: UN 1993

**UN proper shipping name:** Flammable Liquid, n.o.s. (contains ethanol)

Transport hazard class(es): 3
Packing group: III

**Environmental Hazard(s):** Marine Pollutant **Flash Point (°C):** 53.3°C / 128°F

IATA / ICAO

IATA UN / ID No: UN 1993

IATA Proper shipping name: Flammable Liquid, n.o.s. (contains ethanol)

IATA Hazard Class: 3
IATA Packing Group: |||

**IMDG IMDG** 

IMDG UN / ID No: UN 1993

IMDG Proper shipping name: Flammable Liquid, n.o.s. (contains ethanol)

IMDG Hazard Class: 3
IMDG Packing Group: III

Flash Point (°C): 53.3°C / 128°F Environmental Hazard(s): Marine Pollutant

ADR/RID

ADR / RID UN / ID No: UN 1993

ADR/RID Proper shipping Flammable Liquid, n.o.s. (contains ethanol)

name:

ADR / RID Hazard Class: 3
ADR / RID Packing Group: III
ADR / RID Item Number: UN 1993
Environmental Hazard(s): Marine Pollutant

DOT

**DOT Proper shipping name:** Not regulated

## 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

Material Name: Nolvadent® Page 10 of 11
Revision date: 16-Sep-2014 Version: 2.2

# 15. REGULATORY INFORMATION

Canada - WHMIS: Classifications

WHMIS hazard class:

Class B, Division 3

Class D, Division 2, and Subdivision B.

This product has been classified in accordance with the hazard criteria of the CPR and the SDS contains all of the information required by the CPR.



Chlorhexidine acetate

CERCLA/SARA 313 Emission reporting

California Proposition 65

Australia (AICS):

Present

EU EINECS/ELINCS List

200-302-4

Ethyl alcohol (ethanol)

CERCLA/SARA 313 Emission reporting Not Listed

California Proposition 65 carcinogen initial date 4/29/11 in alcoholic beverages

developmental toxicity initial date 10/1/87 in alcoholic beverages

Inventory - United States TSCA - Sect. 8(b)

Australia (AICS):

EU EINECS/ELINCS List

Present
200-578-6

## **16. OTHER INFORMATION**

## Text of R phrases and GHS Classification abbreviations mentioned in Section 3

Acute toxicity, oral-Cat.4; H302 - Harmful if swallowed
Acute toxicity, inhalation-Cat.2; H330 - Fatal if inhaled
Serious eye damage/eye irritation-Cat.2A; H319 - Causes serious eye irritation
Hazardous to the aquatic environment, acute toxicity-Cat.1; H400 - Very toxic to aquatic life
Hazardous to the aquatic environment, chronic toxicity-Cat.1; H410 - Very toxic to aquatic life with long lasting effects
Flammable liquids-Cat.2; H225 - Highly flammable liquid and vapor

Xn - Harmful

Xi - Irritant

T+ - Very toxic

N - Dangerous for the environment

F - Highly flammable

Material Name: Nolvadent® Page 11 of 11
Revision date: 16-Sep-2014 Version: 2.2

R22 - Harmful if swallowed.

R36 - Irritating to eyes.

R26 - Very toxic by inhalation.

R50 - Very toxic to aquatic organisms.

R11 - Highly flammable.

**Data Sources:** The data contained in this SDS may have been gathered from confidential internal sources,

raw material suppliers, or from the published literature.

Reasons for Revision: Updated Section 6 - Accidental Release Measures. Updated Section 8 - Exposure Controls /

Personal Protection. Updated Section 13 - Disposal Considerations.

Prepared by: Toxicology and Hazard Communication Zoetis Global Risk Management

Zoetis Inc. believes that the information contained in this Safety Data Sheet is accurate, and while it is provided in good faith, it is without warranty of any kind, expressed or implied. If data for a hazard are not included in this document there is no known information at this time.

**End of Safety Data Sheet** 

\_\_\_\_\_