

SAFETY DATA SHEETS

This SDS packet was issued with item:

078053312

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

078053320 078912460

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration

(Non-Mandatory Form)

Form Approved

OMB No. 1218-0072



IDENTITY (As Used on Label and LSH)

SUPRAMID Sutures & Implants

Note: Blank spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

S. JACKSON, INC.

Emergency Telephone Number

(703) 370-4900

Address (Number, Street, City, State, and ZIP Code)

P.O. BOX 4487

Telephone Number for Information

(703) 370-4900

ALEXANDRIA VA 22303

Date Prepared

12/10/04

Signature of Preparer (optional)

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))

OSHA PEL

ACGIH TLV

Other Limits
Recommended

% (optional)

NONE

Section III — Physical/Chemical Characteristics

Bailing Point	N/A	Specific Gravity (H ₂ O = 1)	1.13
Vapor Pressure (mm Hg)	N/A	Melting Point	170-250°C
Vapor Density (Air = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	0

Solubility in Water

INSOLUBLE

Appearance and Odor

CLEAR (MAY BE DIED BLACK) - NO ODOR

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used)	400°C	Flammable Limits	LEL 450°C	UEL 500°C
---------------------------	-------	------------------	--------------	--------------

Extinguishing Media

WATER, FOAM, DRY EXTINGUISHING MEDIA

Special Fire Fighting Procedures

The following can be given off at temps above 300°C: TOXIC GASES, CARBON

MONOXIDE. IN ADDITION SMALL QUANTITIES OF HYDROGEN CYANIDE CAN BE FORMED.

Unusual Fire and Explosion Hazards

NON EXPLOSIVE

Stability	Unstable		Conditions to Avoid STARTS TO DECOMPOSE AT 100°C
	Stable	x	AT ROOM TEMPERATURE

Hazardous Decomposition or Byproducts CARBON MONOXIDE, HYDROGEN CYANIDE POSSIBLE TRACES

Hazardous Polymerization	May Occur		Conditions to Avoid	N/A
	Will Not Occur	XXX		

Point(s) of Entry:	Inhalation?	Skin?	Ingestion?
--------------------	-------------	-------	------------

Health Hazards (Acute and Chronic) N/A

Carcinogenicity:	N/A	NTP?	N/A	IARC Monographs?	N/A	OSHA Regulated?	N/A
------------------	-----	------	-----	------------------	-----	-----------------	-----

Signs and Symptoms of Exposure	N/A
--------------------------------	-----

Medical Conditions
Generally Aggravated by Exposure N/A

On skin contact: burns caused by molten material require hospital treatment.

Slept to Be Taken in Case Material Is Released or Spilled
Sweep, shovel up to prevent slipping

Check for possible recycling: can be dumped with domestic refuse or incinerated in suitable plant in accordance with local regulations.

Protection against fire and explosion: Take precautionary measures against static discharges.

Other Precautions	N/A
-------------------	-----

Respiratory Protection (Specify Type)	N/A
---------------------------------------	-----

Ventilation	Local Exhaust	Special
N/A	Mechanical (General)	Other

Protective Gloves	N/A	Eye Protection	N/A
-------------------	-----	----------------	-----

Other Protective Clothing or Equipment	N/A
--	-----

Work/Hygiene Practices	N/A
------------------------	-----