# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

078481165

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

078435509



This Material Safety Data sheet is not intended for consumers and does not address consumer use of the product. For information regarding consumer applications of this product, refer to the product labeling.

# 1. PRODUCT & COMPANY IDENTIFICATION

**Product Name:** Detachol® Adhesive Remover

**Manufacturer:** Ferndale Laboratories, Inc.

780 West Eight Mile Road

Ferndale, Michigan 48220-2498

**Emergency Telephone:** For emergency involving spill, leak, fire exposure or accident, call

CHEMTREC (800) 424-9300, day or night

**Product Technical and** 

**Medical Information:** (800) 621-6003

2. COMPOSITION/HAZARDOUS INGREDIENTS (OSHA-regulated, present at ≥ 1%)						
Chemical Name	CAS Number	Percent (by weight)	Exposure Limit in Air (TWA - 8 hours a day/ 5 day work week)			
Odorless Mineral Spirits Naphtha (petroleum), hydrotreated heavy	64742-48-9	<100%	1200 mg/m <sup>3</sup> / 175 ppm (Exxon)			

**Listed Carcinogens:** The following components, present at concentrations of ≥0.1% are listed as carcinogens or potential carcinogens by either the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), OSHA or ACGIH: None.

3. HAZARDS IDENTIFICATION			
	<u>Health</u>	<u>Flammability</u>	<u>Reactivity</u>
National Fire Protection Association (NF) (estimated)	<b>PA</b> ) 1	2	0

This material is HAZARDOUS by OSHA Hazard Communication guidelines.

# **Emergency Overview**

**Appearance:** Clear orange liquid

**Odor:** Characteristic

**Potential Health Effects** 

**Inhalation:** High vapor concentrations may cause headaches, dizziness, anesthesia,

drowsiness, unconsciousness, and other central nervous system effects.

**Eye Contact:** May cause irritation.

**Skin Contact:** Repeated or prolonged contact may cause skin dryness or cracking.

**Ingestion:** May be aspirated and cause lung damage.

#### 4. FIRST AID MEASURES

**Inhalation:** Remove from further exposure. Use adequate respiratory protection. If respiratory

irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a medical device or use

mouth-to-mouth resuscitation.

**Eyes:** Immediately flush eyes with plenty of water. If irritation occurs, get medical attention.

**Skin:** Wash contact areas with soap and water. Remove contaminated clothing. Launder

contaminated clothing before reuse.

**Ingestion:** Seek immediate medical attention. Do not induce vomiting.

# 5. FIRE FIGHTING

Flammable Properties: Flash Point: > 129°F / > 54°C

Flammable Limits (volume % in air): LEL: 0.7 UEL: 5.3

**Autoignition Temperature:** 475°F (246°C)

**Extinguishing Media:** Water fog, CO<sub>2</sub>, foam or dry chemical

**Special Fire Fighting** 

Procedures:

Hazardous material. Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. Vapors are flammable and heavier than air, may travel across the ground and reach remote ignition sources causing a flashback fire

danger.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal Protection:** Avoid contact with spilled material. See Section 4 for First Aid advice.

Use personal protection recommended in Section 8 of the MSDS.

**Notification Procedure:** U.S. regulations require reporting releases of this material to the

environment which exceed the applicable reportable quantity which could reach any waterway. The National Resource Center can be

reached at (800) 424-8802.

**Spill Cleanup Methods:** Prevent entry into sewers, basements or confined areas. A vapor

suppressing foam may be used to reduce vapors. Use clean non-sparking tools to collect absorbed material. Absorb or cover with dry

earth, sand or other non-combustible material and transfer to

containers.

# 7. HANDLING AND STORAGE

**Handling:** Store at controlled room temperature between 59-86°F (15-30°C)

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Adequate ventilation so that exposure limits are not exceeded.

**Respiratory Protection:** Not applicable; aerosol formation is extremely unlikely for normal use.

When handling large quantities an approved respirator may be used if

engineering controls do not maintain airborne contaminant

concentrations at a level to adequately protect a workers health.

**Eye Protection:** None required during normal administration or use of Detachol®

Adhesive Remover. When handling large quantities, use approved eye

protection to safeguard against potential eye contact.

**Protective Clothing:** Prolonged skin contact may require protective gloves.

**Hygienic Work Practices:** Wash hands thoroughly after handling. If working with large quantities

of Detachol<sup>®</sup> Adhesive Remover (such as spill clean-up), use chemical and oil resistant gloves and clothing, and appropriate eye protection.

No eating, drinking or smoking in area.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Clear orange liquid **pH:** Essentially neutral

# 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal ambient and anticipated storage and handling

conditions of temperature and pressure.

**Conditions to avoid:** Avoid heat, sparks, open flames and other ignition sources.

**Materials to avoid:** Avoid contact with strong oxidizing agents.

**Hazardous Decomposition** 

**Products:** Material does not decompose at ambient temperatures.

**Hazardous Polymerization:** Will not occur.

#### 11. TOXICOLOGICAL INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

## 12. ECOLOGICAL INFORMATION

Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Not expected to be harmful to aquatic organisms or demonstrate chronic toxicity to aquatic organisms.

### 13. DISPOSAL RECOMMENDATIONS

For small quantities, product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Disposal of the used product may also be regulated due to ignitability, corrosivity, reactivity or toxicity as determined by the Toxicity Characteristic Leaching Procedure (TCLP). For large quantities, any disposal practice must be in compliance with local, state, and federal

laws and regulations (contact local or state environmental agency for specific rules). Do not dispose of via sinks, drains, or into immediate environment.

# 14. TRANSPORT INFORMATION

Regulatory classification of this product varies.

**Land (DOT):** Flammable liquid or combustible liquid. This material is not

regulated under 49 CFR in a container of 119 gallons or less.

**Land (TDG):** Flammable liquid or combustible liquid. This material is not

regulated under 49 CFR in a container of 119 gallons or less.

**Sea (IMDG):** This product is considered a flammable liquid. Bulk or non-bulk

packaging: UN1268, Petroleum Distillates, N.O.S., 3, PG III

**Finished Product:** Shipped under Consumer Commodity

**Air (IATA/IMO):** This product is considered a flammable liquid. Bulk or non-bulk

packaging: UN1268, Petroleum Distillates, N.O.S., 3, PG III

Finished Product: Shipped under Consumer Commodity

# 15. REGULATORY INFORMATION

**TSCA:** Exempt

**CERCLA:** This product contains no components subject to reporting or

notification requirements.

SARA (311/312) Reportable

Hazard Category: Fire

SARA (313) Toxic Release This product contains no chemicals subject to the supplier

**Inventory:** notification requirements.

## 16. OTHER INFORMATION

Date Issued: May 12, 2010 Supersedes Date: November 3, 2008

MSDS: 0513, Detachol® Adhesive Remover

**Notice:** The preceding information is based on available data compiled by the manufacturer from its own studies and the work of others and is believed to be correct. However, no warranty is expressed or implied as to the accuracy, completeness or adequacy of this information, the results to be obtained from the use thereof or the hazards connected with the use of the material. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, Ferndale Laboratories, Inc. does not assume any responsibility for the results of its use. The information is furnished upon the condition that the persons receiving it shall make their own determination as to the suitability of the product for their particular use.